

## Ball Valve - Locking Lever

Nickel Plated Body, Brass Ball & Stem, PTFE Seats, Full Bore, Blue Lever, Screwed BSPP, M5 Tapped Vent Hole

### Pressure/Temperature Ratings

Pressure	PN14
Temperature	-10° C to 100° C

### Material List

Description	Material
Body	Brass, Nickel Plated
Seat	PTFE
Ball	Brass, Chrome Plated
End Cap	Brass, Nickel Plated
Stem	Brass, Nickel Plated
Gland Nut	Brass, Nickel Plated
Nut	Geomet®
Gland Seal	PTFE
Washer	PTFE
Handle	PVC Coated Steel

### Dimensions

DN	Size	I	L	G	A	H	CH	Kg
8	1/4"	12	45	22.5	96	48.5	20	0.21
10	3/8"	12	45	22.5	96	48.5	20	0.21
15	1/2"	15.5	59	29.5	96	51	25	0.33
20	3/4"	17	64	32	117	60	31	0.5
25	1"	21	81	40.5	117	64	40	0.84
32	1 1/4"	23	93	46.5	156.5	80	49	1.2
40	1 1/2"	23	102	51	156.5	86	54	1.64
50	2"	26.5	121	60.5	156.5	93	68.5	2.67

