

## Ball Valve - Locking Lever

Nickel Plated Body, Brass Ball & Stem, PTFE Seats, Full Bore, Blue Lever, Screwed BSPP

### Pressure/Temperature Ratings

Pressure	PN40
Temperature	-40° C to 170° C

### Material List

Description	Material	No.
Body	Brass, Nickel Plated	1
Seat	PTFE	2
Ball	Brass, Chrome Plated	3
End Cap	Brass, Nickel Plated	4
Stem	Brass, Nickel Plated	5
Gland Nut	Brass, Nickel Plated	6
Nut	Geomet®	7
Gland Seal	PTFE	8
Washer	PTFE	9
Handle	PVC Coated Steel	10

### Dimensions

DN	Size	I	L	C	A	H	CH	Kg
8	1/4"	12	45	22.5	82	39.5	20	0.21
10	3/8"	12	45	22.5	82	39.5	20	0.21
15	1/2"	15.5	59	29.5	100	43	25	0.33
20	3/4"	17	64	32	120	50.5	31	0.5
25	1"	21	81	40.5	120	54.5	40	0.84
32	1 1/4"	23	93	46.5	158	76	49	1.2
40	1 1/2"	23	102	51	158	82	54	1.64
50	2"	26.5	121	60.5	158	89	68.5	2.67

