

## CUPS WITH SUPPORT

*These traditional cup-shaped vacuum cups are suited for gripping and handling small objects with flat, slightly concave or convex surfaces.*


*This series of widely used cups have diameters ranging from 25 to 35 mm and are normally available in standard compounds: natural para rubber N, oil-resistant rubber A and silicon S.*

*They can be cold-assembled with no adhesive onto a nickel-plated brass support.*

*The support has been specially shaped to perfectly fit with the cup and it is equipped with a male threaded pin to optimise the fastening to the machine.*

*These cups are extremely easy to replace; for the spare part, in fact, all you have to do is request the cup indicated in the table in the desired compound.*

*Cups in special compounds indicated at page 21 and supports in different materials can be provided upon request in minimum quantities to be defined in the order..*



CUPS WITH SUPPORT

Art.	Force	A	SW	D	Cup	Support	Weight
	Kg	∅		∅	Art.	Art.	g
<b>08 25 10 *</b>	1.23	M6	3	25	01 25 10	00 08 08	3.9
<b>08 25 11 *</b>	1.23	G1/8"	4	25	01 25 10	00 08 60	6.8
<b>08 30 10 *</b>	1.76	M6	3	30	01 30 10	00 08 08	4.6
<b>08 30 11 *</b>	1.76	G1/8"	4	30	01 30 10	00 08 60	7.5
<b>08 35 10 *</b>	2.40	M6	3	35	01 35 10	00 08 08	5.1
<b>08 35 11 *</b>	2.40	G1/8"	4	35	01 35 10	00 08 60	8.0

\* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon