

## CUPS WITH SUPPORT

*These traditional cup-shaped vacuum cups are suited for gripping and handling small objects with flat, slightly concave or convex surfaces.*

*This series of widely used cups have diameters ranging from 45 to 60 mm and are normally available in standard compounds: natural para rubber N, oil-resistant rubber A and silicon S.*

*They can be cold-assembled with no adhesive onto an anodised aluminium support.*

*The support has been specially shaped to perfectly fit with the cup and it is equipped with a male threaded pin to optimise the fastening to the machine. Moreover, those with 1/4" thread have an M8 threaded hole, to allow the possible insertion of a calibrated grub screw (see page 1.118) to reduce the amount of sucked air. These cups are extremely easy to replace; for the spare part, in fact, all you have to do is request the cup indicated in the table in the desired compound.*

*Cups in special compounds indicated at page 21 and supports in different materials can be provided upon request in minimum quantities to be defined in the order.*



CUPS WITH SUPPORT

Art.	Force Kg	A Ø	D Ø	M Ø	Cup Art.	Support Art.	Weight g
<b>08 45 10 *</b>	3.98	G1/4"	45	M8	01 45 10	00 08 22	12.6
<b>08 45 11 *</b>	3.98	G1/8"	45	--	01 45 10	00 08 44	11.8
<b>08 45 12 *</b>	3.98	M6	45	--	01 45 10	00 08 313	10.0
<b>08 45 13 *</b>	3.98	M8	45	--	01 45 10	00 08 314	11.0
<b>08 45 14 *</b>	3.98	M10	45	--	01 45 10	00 08 92	11.9

\* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon

