

LV 2270

Brass Spring Check Valve

Full Flow Check Valve, NBR Seal, Polyacetal Disc, Screwed BSPP Female

| Pressure/Temperature Ratings | | |
|------------------------------|---------------|------|
| Pressure | ½" to ¾" | PN40 |
| | 1" to 1¼" | PN25 |
| | 1½" to 2" | PN16 |
| Temperature | -10°C to 90°C | |



| Material List | |
|---------------|--------------------------|
| Body | Brass CW617N |
| End Connector | Brass CW617N |
| Disc | P.O.M |
| Disc Holder | P.O.M |
| Spring | Stainless Steel AISI 302 |

| Dimensions | | | | | |
|------------|----|-------|------|------|------|
| Size | Ø | H | L | F | Kg |
| ½" | 15 | 56.3 | 30.5 | 16.5 | 0.13 |
| ¾" | 20 | 61 | 38 | 17.4 | 0.19 |
| 1" | 25 | 74.8 | 46.5 | 20.7 | 0.32 |
| 1¼" | 32 | 93.5 | 56.5 | 22.5 | 0.56 |
| 1½" | 40 | 99.4 | 68 | 22.8 | 0.83 |
| 2" | 50 | 109.9 | 83 | 27 | 1.25 |

