



LV 5310T  
LV 5311L

## Ball Valve, Three-Way, T-Port / L-Port

Nickel Plated Body, Screwed BSPP Female,  
Reduced Bore, Lever Operated



L-Port  
Configuration



T-Port  
Configuration

### Pressure/Temperature Ratings

Pressure	1/4" - 3/8" 55 Bar
	1/2" - 3/4" 50 Bar
	1" 45 Bar
	1 1/4" - 2" 35 Bar
	2 1/2" 40 Bar
	3" 16 Bar
Temperature	1/4" - 2" -10°C to 120°C
Temperature	2 1/2" - 3" -15°C to 100°C

### Material List 1/4" - 2"

Body	Brass Nickel Plated
Ball	Brass Chrome Plated
Seats	PTFE
Stem	Brass
Stem O-Ring 1/4" - 2"	NBR
Stem O-Ring 2 1/2" - 3"	Viton
Handle	Aluminium

### Dimensions 1/4" - 2"

Size	B	D	E	F	G	H	CH	DN
1/4"	65	38.5	77	125	75	22	22	10
3/8"	65	38.5	77	125	75	22	22	12
1/2"	65	38.5	77	125	75	22	27	14
3/4"	83	46	92	145	91	25	34	18
1"	96	52	104	170	105	30	41	23
1 1/4"	102	59	118	170	115	34	50	29
1 1/2"	109	69	138	170	128	40	57	36
2"	139	81	162	260	165	48	70	45

### Dimensions 2 1/2"

DN	L	L2	Ø	I	H	M
2 1/2"	194	97	50	35	124	240

### Dimensions 3"

DN	Size	ØD	A	B min	B max	ØC	E	F	L
80	3"	44	235	129	141	95	47	148	202

