




Other designs in series 25

The following other designs can be found from page:

- Stainless Steel P. 208
- Safety P. 274
- Safety Self-Venting P. 294
- Coded Systems P. 302










Technical Description

Universal industrial coupling with standard European profile. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use.

Dust Protections  (P. 319) for Coupling Part.-No. SK23S for Plug Part.-No. SK12S

Working Temperature*
-20°C up to +100°C (NBR) depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

		
<p>Working Pressure** 35 bar ** maximum static working pressure with safety factor 4 to 1.</p>	<p>35 bar</p>	<p>8 bar</p>
<p>Features</p> <ul style="list-style-type: none"> • Brass coupling and plug for use with water • Robust coupling system with steel sleeve 		<ul style="list-style-type: none"> • Minimal, almost imperceptible leakage when uncoupling • No air locked into the system during the coupling process • Brass valved plug available blank
<p>Material Coupling: Brass / Steel nickel plated Plug: Steel zinc plated or Brass (Serie 26) Seals: NBR</p>	<p>Coupling: Brass Plug: Brass Seals: NBR</p>	<p>Coupling: Brass nickel plated Plug: Brass nickel plated Seals: NBR</p>
<p>Interchangeability</p> <ul style="list-style-type: none"> • Rectus 26 • Rectus 1600/1625 • Cejn 320 • JWL 520 + JWL 530 • various German Products 		
<p>Flow diagrams</p> <p>Air</p>  <p>Water</p> 	<p>Air</p>  <p>Water</p> 	<p>Air</p>  <p>Water</p> 



	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number	
<p>Female Thread</p>	M 16 x 1,5	22		43	9					blank	25SBIM16MPX	
	M 16 x 1,5	22		43	9					nickel plated	25SBIM16MPN	
	M 18 x 1,5	22		43	9					blank	25SBIM18MPX	
	M 18 x 1,5	22		43	9					nickel plated	25SBIM18MPN	
<p>Hose Barb</p>	6 mm	21		60	25					blank	25SBTF06MPX	
	6 mm	21		60	25					nickel plated	25SBTF06MPN	
	8 mm	21		60	25					blank	25SBTF08MPX	
	8 mm	21		60	25					nickel plated	25SBTF08MPN	
	9 mm	21		60	25					blank	25SBTF09MPX	
	9 mm	21		60	25					nickel plated	25SBTF09MPN	
	10 mm	21		60	25					blank	25SBTF10MPX	
	10 mm	21		60	25					nickel plated	25SBTF10MPN	
	13 mm	21		60	25					blank	25SBTF13MPX	
	13 mm	21		60	25					nickel plated	25SBTF13MPN	
	6 mm Parker	19		67,5	20,5						blank	25SBTP06MPX
	6 mm Parker	19		67,5	20,5						nickel plated	25SBTP06MPN
	10 mm Parker	19		71	24						blank	25SBTP10MPX
	10 mm Parker	19		71	24						nickel plated	25SBTP10MPN
13 mm Parker	19		83	28						blank	25SBTP13MPX	
13 mm Parker	19		83	28						nickel plated	25SBTP13MPN	
<p>with Plastic Hose Connection</p>	4 x 6 mm	21		47	7	6			M 10 x 1	blank	25SBKO06MPX	
	4 x 6 mm	21		47	7	6			M 10 x 1	nickel plated	25SBKO06MPN	
	6 x 8 mm	21		47	7	6			M 12 x 1	blank	25SBKO08MPX	
	6 x 8 mm	21		47	7	6			M 12 x 1	nickel plated	25SBKO08MPN	
	8 x 10 mm	21		51	8,5	8,5			M 16 x 1	blank	25SBKO10MPX	
	8 x 10 mm	21		51	8,5	8,5			M 16 x 1	nickel plated	25SBKO10MPN	
	9 x 12 mm	21		51	8,5	8,5			M 16 x 1	blank	25SBKO12MPX	
	9 x 12 mm	21		51	8,5	8,5			M 16 x 1	nickel plated	25SBKO12MPN	
<p>Panel Mount with Hose Barb</p>	6 mm	21	17	62	17	10		4	M 12 x 1	blank	25SBTS06MPX	
	6 mm	21	17	62	17	10		4	M 12 x 1	nickel plated	25SBTS06MPN	
	8 mm	21	17	65	17	14		4	M 12 x 1	blank	25SBTS08MPX	
	8 mm	21	17	65	17	14		4	M 12 x 1	nickel plated	25SBTS08MPN	
	10 mm	21	17	74	25	14		3,5	G 1/4	blank	25SBTS10MPX	
	10 mm	21	17	74	25	14		3,5	G 1/4	nickel plated	25SBTS10MPN	
<p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm	19		120	7	6			M 10 x 1	blank	25SBKK06MPX	
	4 x 6 mm	19		120	7	6			M 10 x 1	nickel plated	25SBKK06MPN	
	6 x 8 mm	19		135	7	6			M 12 x 1	blank	25SBKK08MPX	
	6 x 8 mm	19		135	7	6			M 12 x 1	nickel plated	25SBKK08MPN	
	8 x 10 mm	19		145	8,5	8,5			M 16 x 1	blank	25SBKK10MPX	
	8 x 10 mm	19		145	8,5	8,5			M 16 x 1	nickel plated	25SBKK10MPN	
	9 x 12 mm	19		150	8,5	8,5			M 16 x 1	blank	25SBKK12MPX	
	9 x 12 mm	19		150	8,5	8,5			M 16 x 1	nickel plated	25SBKK12MPN	